

Wind Ward LLVG

Freeway Dock or Structure


Arterial Railroad Navigation Channel


Bridge Study Area
Upland ECSI Site (2008)
Background Taxlot (7/08) River or slough

Portland Harbor RI/FS Baseline Ecological Risk Assessment

DO NOT QUOTE OR CITE

This document is currently under review by US EPA and its federal, state, and tribal partners, and is subject to change in whole or in part.





Sediment Transport


LPA is in a depositional reach of Portland Harbor, as shown by the higher percentage of fine-grained sediment, bathymetric changes from 2002 to 2009, and sediment transport modeling.

Characteristic grain sizes adjacent to LPA

Finer-grained sediments indicate depositional environments. Sediment particle sizes adjacent to LPA are dominated by silts, particularly subsurface sediment which consistently ranges between 60-80% fines. Coarser fractions indicate a higher energy scour zone upstream of LPA from river mile (RM) 5 to 7, from which sediments are likely to be eroded.




Surface sediment composition




Shallow (30 cm) subsurface sediment composition (Map 3.4-3)

KNOTA

Measured Bathymetric Changes River bottom elevation changes were compared over a 7 year period to determine where erosion and deposition have occurred. Net deposition of sediment was documented offshore of LPA. amounting to 2 to 5 feet in many areas indicating contaminated sediment transported from upstream sources may have been deposited adjacent to



Bathymetric change from July 2002 to January 2009



0.25 to 0.5 ft de

Maximum modeled erosion for high flow scenario

Sediment Transport Modeling A hydrodynamic and sediment transport model was used in the RI to predict maximum erosion and deposition under different flow conditions. For a major flood event of 160,000 cfs¹, deposition of up to 0.5 to 2.0 feet off the shoreline of LPA was predicted, supporting the bathymetric changes measured during the RI. Significant erosion (of 10 feet or more) was predicted for the high energy zone upstream from LPA, where significant contamination is present.

1 Mean daily flows of approximately 160,000 cfs or more were recorded on 119 days (0.9 percent) over the 30-year period of record and on 14 days (0.5 percent) over the RI water years 2001 through March 31, 2008.

LOWER WILLAMETTE GROUP

Transportation, Property, or Boundaries: Metro RLIS. Channel & River Miles: US Army Corps of Engineers

--- River Miles Navigation Channel River Edge +13 ft NAVD Bridges Docks and Structures

Upland ECSI Sites (2008) Waterfront Taxlots

DRAFT

DO NOT QUOTE OR CITE
This document is currently under review by US EPA and its federal, state, and tribal partners, and is subject to change in whole or in part.

Map 3.5-3 Portland Harbor RI/FS

Draft Remedial Investigation Report Study Area Grain Size, Bathymetric Change, and Modeled Maximum Erosion

